



FEATURES

- Plastic package has Underwriters Laboratory Flammability Classification 94V-0
- Metal silicon junction ,majority carrier conduction
- Guard ring for overvoltage protection
- Low power loss ,high efficiency
- High current capability ,Low forward voltage drop
- Single rectifier construction
- High surge capability
- For use in low voltage ,high frequency inverters, free wheeling ,and polarity protection applications
- High temperature soldering guaranteed:260°C/10 seconds, 0.25"(6.35mm)from case
- Component in accordance to RoHS 2002/95/EC and WEEE 2002/96/EC



TO-277



Dimensions in inches and (millimeters)

MECHANICAL DATA

Case : Packed with FRP substrate and epoxy underfilled

Terminals : Pure Tin plated (Lead-Free), solderable per MIL-STD-750, Method 2026.

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS


(Ratings at 25°C ambient temperature unless otherwise specified ,Single phase ,half wave ,resistive or inductive load. For capacitive load,derate by 20%.)

	Symbols	SP 1020L	SP 1030L	SP 1040L	SP 1050L	SP 1060L	SP 1080L	SP 10100L	SP 10150L	SP 10200L	Units
Maximum repetitive peak reverse voltage	V_{RRM}	20	30	40	50	60	80	100	150	200	Volts
Maximum RMS voltage	V_{RMS}	14	21	28	35	42	56	70	105	140	Volts
Maximum DC blocking voltage	V_{DC}	20	30	40	50	60	80	100	150	200	Volts
Maximum average forward rectified current (see Fig.1)	$I_{(AV)}$	10.0									Amps
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC method)	I_{FSM}	150.0									Amps
Maximum instantaneous forward voltage at 10.0 A(Note 1)	V_F	0.45		0.55			0.80		0.85	0.90	Volts
Maximum instantaneous reverse current at rated DC blocking voltage(Note 1)	$T_a = 25^\circ\text{C}$	0.2									mA
	$T_a = 125^\circ\text{C}$	15			50						
Typical thermal resistance (Note 2)	$R_{\theta JC}$	2.5									°C/W
Operating junction temperature range	T_J	-65 to +150									°C
Storage temperature range	T_{STG}	-65 to +150									°C

Notes: 1.Pulse test: 300 μ s pulse width,1% duty cycle


2.Thermal resistance from junction to case

FIG.1-FORWARD CURRENT DERATING CURVE




LEAD TEMPERATURE(°C)

FIG.3-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




INSTANTANEOUS FORWARD VOLTAGE (VOLTS)

FIG.5-TYPICAL JUNCTION CAPACITANCE




REVERSE VOLTAGE, VOLTS

FIG.2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




NUMBER OF CYCLES AT 60Hz

FIG.4-TYPICAL REVERSE CHARACTERISTICS



PERCENT OF RATED PEAK REVERSE VOLTAGE%

FIG.6-TYPICAL TRANSIENT THERMAL IMPEDANCE



T, PULSE DURATION ,sec.